"STANDARD K.D." DOUBLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. SK -2) LOCKER DETAILS: FIFVATION ' ' DOOR & FRAME COLOR = BODY COMPONENT COLOR = 729 PARCHMENT TNP = HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR VENTILATION = 3' LOUVERS SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = CONTINUOUS PIANO HINGE. CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL. GAUGES 16 GA., C.R.S. DOOR = (9" WIDE DOOR = 18 GA., C.R.S.) FRAME = 16 GA., C.R.S TOP = 24 GA., C.R.S. 24 GA., C.R.S. BOTTOM = 24 GA., C.R.S. SHELVES = SIDES = 24 GA., C.R.S. : BACKS = 24 GA., C.R.S. LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36" TO 20" TALL DOORS. SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL Checked By: Drawn By: Customer: CUSTOMER PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DRAFTER DATE NONE | Hallowell[®] DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION, ONLY LIST INDUSTRIES Customer Order Number: PO# RESERVES THE RIGHT TO ALTER ANY DESIGN, ANY UNAUTHORIZED Sheet # Of # Revision: Acad Number: PAGE NUMBER MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES. Description:

TOLERANCES UNLESS SPECIFIED

DECIMALS: ±.010

DEGREES: ±1°

FRACTIONS: ±1/32

JOB NAME

JOB LOCATION

Drawing Number:

FOLDER NUMBER