## PREMIUM KD FIVE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. SK -5) LOCKER DETAILS: ELEVATION ' ' DOOR & FRAME COLOR = BODY COMPONENT COLOR = 729 PARCHMENT HANDLE = FRICTION CATCH FINGER PULL DOOR VENTILATION = 3" LOUVERS SIDE VENTILATION = SOLID BASE = LOCKS = HINGE = CONTINUOUS PIAND HINGE $\equiv$ CONTRACTOR NOTE ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS, ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE $\equiv$ THE BASE. LITCKERS MUST BE ANCHORED TO WALL. GAUGES 18 GA., C.R.S. DOOR = 16 GA., C.R.S FRAME = TOP = 24 GA., C.R.S. BOTTOM = 24 GA., C.R.S. SHELVES = 24 GA., C.R.S. $\equiv$ SIDES = 24 GA., C.R.S. BACKS = 24 GA., C.R.S. $\equiv$ LATCHING: (BOX DOOR) SINGLE POINT FRICTION CATCH WITH DOOR PULL, DOOR WILL ACCEPT BUILT-IN LOCK OR PADLOCK. SIDE VIEW FRONT VIEW THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL Checked By: Drawn By: Customer: CUSTOMER PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DRAFTER DATE NONE **Hallowell** DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION, ONLY LIST INDUSTRIES Customer Order Number: PO# RESERVES THE RIGHT TO ALTER ANY DESIGN, ANY UNAUTHORIZED Revision: Acad Number: PAGE NUMBER Sheet # Of # MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES. Description: JOB NAME Drawing Number: FOLDER NUMBER TOLERANCES UNLESS SPECIFIED JOB LOCATION

FRACTIONS: ±1/32

DECIMALS: ±.010

DEGREES: ±1°